


# REQUEST TO EXIT STATIONS FOR MAGNETIC LOCKS AND ELECTRIC DOOR STRIKES

## MODEL TS-6

- GREEN .675 x .875 INCH PUSHBUTTON
- LABELED "PUSH TO EXIT"
- RED, GREEN LEDS, OPERATE ON 12 OR 24 VDC, INDEPENDENTLY WIRED
- MOMENTARY ACTION SWITCH
- SWITCH ILLUMINATED WITH HIGH BRIGHTNESS LED, OPERATES ON 12 OR 24 VOLTS AC/DC
- D.P.D.T. CONTACTS RATED 3 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.25 INCHES
- UL APPROVED AND CSA CERTIFIED COMPONENTS



## MODEL TS-7

- GREEN .675 x .875 INCH PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- SWITCH ILLUMINATED WITH HIGH BRIGHTNESS LED, OPERATES ON 12 OR 24 VOLTS AC/DC
- D.P.D.T. CONTACTS RATED 3 AMP. @ 35 VDC OR 120 VAC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- TEMPERATURE RANGE - 25C TO + 70C
- SWITCH DEPTH 1.25 INCHES
- UL APPROVED AND CSA CERTIFIED COMPONENTS



## MODEL TS-8

- GREEN .675 x .875 INCH PUSHBUTTON
- LABELED "PUSH TO EXIT"
- RED, GREEN LEDS, OPERATE ON 12 OR 24 VDC, INDEPENDENTLY WIRED
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 3 AMP. @ 35 VDC OR 120 VAC
- SWITCH ILLUMINATED WITH HIGH BRIGHTNESS LED, OPERATES ON 12 OR 24 VOLTS AC/DC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON NARROW 1.75 INCH 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.25 INCHES
- UL LISTED AND CSA CERTIFIED COMPONENTS



## MODEL TS-9

- GREEN .675 x .875 INCH PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 3 AMP. @ 35 VDC OR 120 VAC
- SWITCH ILLUMINATED WITH HIGH BRIGHTNESS LED, OPERATES ON 12 OR 24 VOLTS AC/DC
- SWITCH TERMINATED WITH COLOR CODED LEADS
- SWITCH MOUNTED ON NARROW 1.75 INCH 302 STAINLESS STEEL WALLPLATE
- TEMPERATURE RANGE - 25C TO + 70C
- SWITCH DEPTH 1.25 INCHES
- UL LISTED AND CSA CERTIFIED COMPONENTS



**SPECIFY  
MODEL TS-9L  
FOR LATCHING  
SWITCH**

## MODEL TS-25

### EMERGENCY DOOR RELEASE METHOD OF OPERATION

PRESSING THE LATCHING PUSHBUTTON WILL SOUND THE BUZZER AND LIGHT THE SWITCH. THE CONTACTS WILL TRANSFER PROVIDING A CIRCUIT TO RELEASE THE DOOR. PRESSING THE PUSHBUTTON AGAIN WILL RETURN THE DOOR TO THE LOCKED POSITION AND TURN OFF THE LIGHT AND BUZZER.

- RED .675 x .875 INCH PUSHBUTTON LABELED "PUSH"
- PLATE LABELED "EMERGENCY DOOR RELEASE, ALARM WILL SOUND"
- S.P.D.T. LATCHING ILLUMINATED PUSHBUTTON, CONTACTS RATED 3 AMP. @ 35 VDC OR 120 VAC, 85 Db PIEZO BUZZER
- 12 OR 24 VOLT DC OPERATION
- MOUNTED ON SINGLE GANG WALLPLATE



**SPECIFY  
MODEL TS-26  
FOR 1.75"  
WIDE  
WALLPLATE**

## MODEL TS-32

### EMERGENCY DOOR RELEASE

- RED 1.5" DIA. MUSHROOM BUTTON
- LABELED "EMERGENCY DOOR RELEASE"
- LATCHING ACTION SWITCH
- ONE NORMALLY-OPEN AND ONE NORMALLY-CLOSED CONTACT
- CONTACTS RATED 10 AMP. @ 35 VDC OR 120 VAC
- SCREW TERMINALS
- SWITCH DEPTH 2 INCHES
- SWITCH MOUNTED ON SINGLE GANG STAINLESS STEEL WALLPLATE
- UL AND CSA CERTIFIED COMPONENTS
- MUSHROOM BUTTON ALSO AVAILABLE IN BLACK OR GREEN



**SPECIFY  
MODEL TS-32B  
FOR BLACK  
MODEL TS-32G  
FOR GREEN**