DTCDesktop Console





Desktop Console with single or multiple switch configurations. Choose between momentary action switches that remain active as long as they're depressed or alternate action switches that alternate between open (disconnected) and closed (connected) each time they're pressed. Designed to work with door status or lock status sensors in order to supervise and control several entry points from one main location.

Configurable Options

- M1 with 1-2 switches, specify number of switches when ordering
- M2 with 3-12 switches, specify number of switches when ordering
- M3 with 13-40 switches, specify number of switches when ordering
- Console: specify G (beige) or K (black)
- Switch type, specify: SPDT/DPDT, momentary/ alternate
- Lens color: green, red, yellow, blue, white

- Illumination: None, 12 VDC, 24 VDC
- Button labels available as a custom part

Specifications

Console Dimensions

- M1: 3-3/10"W x 5-7/10"L x 1-1/2"H
- M2: 6-9/10"W x 9-2/5"L x 2-1/2"H
- M3: 14"W x 8-3/10" x 3" (rear)/1-1/2" (front)

Switch Dimensions

• 5/8" x 7/8"

Electrical

- LED current draw:
 9mA nominal
- Contact rated 3A at 24 VDC
- Switches terminated in 22AWG colored 12" leads
 - Common: white
 - N/C: red
 - N/O: blue
 - LED+: Yellow
 - LED-: Black

How To Order

CONSOLE	CONSOLE COLOR	SWITCH QUANTITY	SWITCH TYPE	LENS COLOR	ILLUMINATION
M2	K	6	A	G	V1
M1 1-2 switches	G - Beige	Number of switches required	A - SPDT Momentary Action	G - Green	N - None
M2 3-12 switches	K - Black		B - SPDT Alternate Action	R - Red	V1 - 12VDC
M3 13-40 switches			C - DPDT Momentary Action	Y - Yellow	V2 - 24VDC
			D - DPDT Alternate Action	B - Blue	
				W - White	

For pricing on custom Desktop Consoles, please contact the factory at 800.645.5538